

X22 5-Way Selectable Floodlight



PERFORMANCE

X22-250@ 250W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	240.4W	242.1W	240.3W	235.5W	235.3W	235.4W	240.8W	241W	240.9W
LUMENS	34,400	34,959	33,238	36,181	36,299	34,874	36,044	36,277	34,754
EFFICACY	143.1	144.4	138.3	153.6	154.3	148.1	149.7	150.5	144.3
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	120-277V								

X22-250@ 250W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	241.1W	240.9W	240.7W	235.2W	234.9W	234.6W	241.6W	241.6W	241.3W
LUMENS	35,541	35,508	33,913	37,095	37,115	35,356	37,207	37,335	35,493
EFFICACY	147.4	147.4	140.9	157.7	158.0	150.7	154.0	154.5	147.1
CRI	82	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	480V								

X22-250@ 220W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	216.6W	217.7W	216.3W	213.0W	212.4W	212.7W	217.8W	217.6W	217.7W
LUMENS	31,578	31,955	30,476	33,014	32,981	31,784	32,889	32,961	31,675
EFFICACY	145.8	146.8	140.9	155.0	155.3	149.4	151.0	151.5	145.5
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	120-277V								

X22-250@ 220W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	208.7W	208.7W	209.0W	204.4W	204.3W	204.5W	210.0W	210.1W	210.4W
LUMENS	31,332	31,445	30,324	32,506	32,671	31,425	32,604	32,865	31,546
EFFICACY	150.1	150.7	145.1	159.0	159.9	153.7	155.3	156.4	149.9
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	480V								

X22 5-Way Selectable Floodlight



PERFORMANCE

X22-250@ 190W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	186.2W	187.1W	186W	183.9W	183.3W	183.7W	188.0W	187.7W	188W
LUMENS	27,898	28,136	26,864	28,961	28,835	27,820	28,851	28,817	27,724
EFFICACY	149.8	150.4	144.4	157.5	157.3	151.4	153.5	153.5	147.5
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	120-277V								

X22-250@ 190W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	180.3W	180.4W	180.4W	177.3W	177.3W	177.2W	182.1W	182.4W	182.3W
LUMENS	27,639	27,737	26,630	28,472	28,615	27,402	28,558	28,785	27,508
EFFICACY	153.3	153.8	147.6	160.6	161.4	154.6	156.8	157.8	150.9
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	480V								

X22-250@ 160W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	158.6W	159.5W	158.6W	157.2W	156.9W	157.2W	160.8W	160.7W	160.9W
LUMENS	24,752	24,545	23,859	25,513	24,976	24,533	25,416	24,961	24,448
EFFICACY	156.1	153.9	150.4	162.3	159.2	156.1	158.1	155.3	151.9
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	120-277V								

X22-250@ 160W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	154.9W	154.9W	155W	152.9W	152.9W	152.9W	157.1W	157.2W	157.3W
LUMENS	24,136	24,224	23,207	24,687	24,814	23,711	24,762	24,961	23,802
EFFICACY	155.8	156.4	149.7	161.5	162.3	155.1	157.6	158.8	151.3
CRI	83	83	83	83	84	84	83	83	83
VOLTAGE RATINGS	480V								