

X22 5-Way Selectable Floodlight



PERFORMANCE

X22-420@ 420W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	415.4W	417.5W	415.7W	404.7W	405.2W	404.4W	417.4W	417.0W	416.6W
LUMENS	60,622	61,054	57,558	63,993	63,853	60,400	64,206	63,706	60,515
EFFICACY	145.9	146.2	138.5	158.1	157.6	149.4	153.8	152.8	145.3
CRI	82	82	83	84	84	83	83	83	83
VOLTAGE RATINGS	120-277V								

X22-420@ 420W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	420.2W	421.3W	420.8W	409.7W	409.9W	409.6W	420.9W	422.2W	422.0W
LUMENS	62,235	62,343	59,037	65,845	65,661	62,299	65,477	65,458	62,056
EFFICACY	148.1	148.0	140.3	160.7	160.2	152.1	155.6	155.0	147.1
CRI	82	82	82	84	84	83	83	83	83
VOLTAGE RATINGS	480V								

X22-420@ 380W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	378.2W	378.5W	376.1W	369.9W	368.8W	367.3W	381.5W	379.6W	378.4W
LUMENS	56,571	56,257	53,017	59,358	58,483	55,301	59,556	58,348	55,406
EFFICACY	149.6	148.6	141.0	160.5	158.6	150.6	156.1	153.7	146.4
CRI	82	82	83	84	84	83	83	83	83
VOLTAGE RATINGS	120-277V								

X22-420@ 380W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	375.2W	376.8W	376.3W	367.3W	368.1W	367.7W	377.3	379.1W	378.9W
LUMENS	56,446	566,71	53,746	59,362	59,329	56,375	59,030	59,146	56,155
EFFICACY	150.4	150.4	142.8	161.6	161.2	153.3	156.5	156.0	148.2
CRI	82	82	83	84	84	83	83	83	83
VOLTAGE RATINGS	480V								

X22 5-Way Selectable Floodlight



PERFORMANCE

X22-420@ 340W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	337.2W	336.8W	336.6W	331.1W	329.5W	330.1W	341.5W	339.1W	340W
LUMENS	51,345	50,930	48,436	53,496	52,572	50,167	53,674	52,451	50,262
EFFICACY	152.3	151.2	143.9	161.6	159.6	152.0	157.2	154.7	147.8
CRI	82	82	83	84	84	83	83	83	83
VOLTAGE RATINGS	120-277V								

X22-420@ 340W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	336.6W	337.9W	337.4W	330.8W	331.4W	331W	339.9W	341.3W	341.1W
LUMENS	51,459	51,661	49,044	53,736	53,703	51,081	53,436	53,537	50,882
EFFICACY	152.9	152.9	145.4	162.4	162.0	154.3	157.2	156.9	149.2
CRI	82	82	83	84	84	83	83	83	83
VOLTAGE RATINGS	480V								

X22-420@ 300W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	295.0W	294.8W	294.7W	290.9W	289.5W	290.1W	300W	298W	298.9W
LUMENS	45,952	45,597	43,487	47,537	46,734	44,722	47,695	46,626	44,807
EFFICACY	155.8	154.7	147.6	163.4	161.4	154.2	159.0	156.5	149.9
CRI	82	82	83	84	84	83	83	83	83
VOLTAGE RATINGS	120-277V								

X22-420@ 300W	3000K			4000K			5000K		
BEAM SETTING	90°	75°	55°	90°	75°	55°	90°	75°	55°
NEMA TYPE	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V	7H X 7V	7H X 6V	6H X 6V
INPUT WATTS	297.3W	299.4W	298.3W	293.3W	294.8W	293.8W	301.4W	303.6W	302.7W
LUMENS	46,153	46,476	44,046	47,854	47,971	45,550	47,586	47,822	45,372
EFFICACY	155.2	155.2	147.7	163.2	162.7	155.0	157.9	157.5	149.9
CRI	82	83	83	84	84	83	83	83	83
VOLTAGE RATINGS	480V								