


RAB®

A22



Interchangeable optics with quality you can trust!

A22—with selectable CCT, wattage, and distribution type.

Changing optics has never been easier.

Available in a wide range of models—everything from 50W to 320W—the A22 comes with interchangeable optics that give you the flexibility to change output in the field. IES Type II, III, IV, and V distributions are all available.



All-in-one maximized versatility.

When you need one fixture to do it all, the A22-150X delivers. In addition to boasting three selectable wattages and color temperatures, and a twistlock photocell, the 150X includes three interchangeable lenses (Types III, IV, V) and an adjustable universal pole mount.

Innovative door design opens/closes with a quick twist and secures the lens against high winds.





100,000-HOUR LED LIFESPAN



5-YEAR LIMITED WARRANTY

RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty

Sensors and controls.

All A22 models come standard with a NEMA 7-pin receptacle but can also be ordered with an integrated microwave sensor to help qualify for additional utility rebates. Standard and Lightcloud twistlock photocells can also be purchased as accessories.



Light an entire site.

Out of the box, the A22 includes an adjustable, universal pole mount, but several other mounting accessories are offered so that it can be used throughout various areas for one unified look.

SLIPFITTER MOUNT



A22SFB



A22SF



A22SFW

WALL MOUNT



A22WMB



A22WM



A22WMW

Interchangeable Optics

	TYPE II	TYPE IV	TYPE V
70 & 100	A22-70/100LENS2T	A22-70/100LENS4T	A22-70/100LENS5T
150 & 200	A22-150/200LENS2T	A22-150/200LENS4T	A22-150/200LENS5T
320	A22-320LENS2T	A22-320LENS4T	A22-320LENS5T

Controls



Twistlock Photocell
R-3P-PCT (120-277V)
R-3P-PCT-480V (480V)



Lightcloud Twistlock Photocell
LCTWIST/K



Remote Control for /MVS Models*

MSR1

*Remote control required for managing settings of the microwave sensor.

Ordering Matrix

Product Family	Optics	Wattages	Color Temp	Mounting	Finish	Voltage	Options		
A22	Blank 2T 4T 5T	Type III Type II Type IV Type V	70 100 150 200 320	70/60/50W 100/80/60W 150/120/100W 200/180/160W 320/280/250W	Blank 3000/4000/5000K CCT Adjustable	Blank Universal Adjustable Pole Mount	Blank W B Bronze White Black	Blank /480 120-277V* 480V*	Blank /MVS 7-Pin Receptacle with Shorting Cap and Microwave Occupancy Sensor /LCBS** Lightcloud Blue Enabled w/PIR Sensor /LCBS/MVS** Lightcloud Blue Enabled w/MVS Sensor

Product Family	Optics	Wattages	Color Temp	Mounting	Finish	Voltage	Options	
A22	Blank	Type III Installed, Type IV and Type V included	150X 150/120/100W	Blank 3000/4000/5000K CCT Adjustable	Blank Universal Adjustable Pole Mount	Blank Bronze	Blank 120-277V, 0-10V Dimming	Blank 7-Pin Receptacle with Shorting Cap and 3-Pin Twistlock Photocell /LCBS** Lightcloud Blue Enabled w/PIR Sensor /LCBS/MVS** Lightcloud Blue Enabled w/MVS Sensor

*0-10V dimming standard

**Only available for bronze models