





















RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty

All the basics are covered.

Available in 4 lumen packages and 3 distributions (Types III, IV, and V) the A34 offers field-selectable wattage and CCT. Select from a universal pole mount, slipfitter, or wall mount to light various site applications with the same, great-looking fixture.

Extra Large (340/270/220W) Large (250/200/150W)

Medium (150/125/100W)



Small (100/80/50W)






WALL MOUNT



SLIPFITTER



All A34 models come standard with an on/off photocell and are available with an optional passive infrared or microwave motion sensor. For more fine-tuned control, both sensors are also offered with Lightcloud Blue compatibility and can quickly integrate with our powerful lighting control system.





Ordering Matrix

Product Family	Distribu	tion Type	Size/Wattage		Mounting		Color Temperature		1	Finish		Voltage Rating		Option	
A34															
	T3 T4 T5	Type III Type IV Type V	S M L XL	Small (100/80/50W) Medium (150/125/100W) Large (250/200/150W) Extra Large (340/270/220W)	SF	Universal Pole Mount Slipfitter Wall Mount	BLANK	3000/4000/5000K Adjustable		Bronze White	BLANK /480 *	120-277V, 0-10V Dimming 480V, 0-10V Dimming	/LCBS	No Option Passive Infrared Sensor Microwave Motion Sensor Lightcloud Blue Enabled w/ PIR Sensor Lightcloud Blue Enabled w/MVS Sensor	