

RAB®

CURV



Flush mounted
and fashionable.

CURV field-adjustable fixtures offer both flexibility and style.

Indoor and outdoor.

UL listed for wet locations under covered ceilings, the CURV works great in canopies and other outdoor applications.



It's all about uniformity.

Diffuse lens produces uniform light and reduces glare.



**5-YEAR
NO COMPROMISE
WARRANTY**
RAB's warranty is
subject to all terms
and conditions found at
rablighting.com/warranty



CURV FA
with decorative ring

12" 14" 18"



CURV FA

11" 14" 19"



Selection and style.

A low-profile design and numerous size options create a look and feel that can match any space.

5-Way field adjustable.

This line of surface mounts is field adjustable, allowing you to choose from five color temperatures with the flick of a switch, giving you the flexibility to customize an area's appearance with a single fixture!

SKUs

CURV Smooth - CRVFAS

Catalog Number	Size	Equivalency	Input Wattage	Input Voltage	Dimming Protocol	Emergency Battery	Sensor
CRVFAS-11R-16-9CCT-120-W	11"	75W Incandescent	16W	120V	TRIAC/ELV	---	---
CRVFAS-11R-16-9CCT-UNVT-W				120-277V	TRIAC/ELV	---	---
CRVFAS-11R-16-9CCT-UNV-W				120-277V	0-10V	---	---
CRVFAS-11R-16-9CCT-UNV-W/MVS				120-277V	0-10V	---	Microwave
CRVFAS-11R-16-9CCT-UNVT-W/EMBB				120-277V	TRIAC/ELV	Yes	---
CRVFAS-11R/MVS/EM				120-277V	0-10V	Yes	Microwave
CRVFAS-14R-20-9CCT-120-W	14"	125W Incandescent	20W	120V	TRIAC/ELV	---	---
CRVFAS-14R-20-9CCT-UNVT-W				120-277V	TRIAC/ELV	---	---
CRVFAS-14R-20-9CCT-UNV-W				120-277V	0-10V	---	---
CRVFAS-14R-20-9CCT-UNV-W/MVS				120-277V	0-10V	---	Microwave
CRVFAS-14R-20-9CCT-UNVT-W/EMBB				120-277V	TRIAC/ELV	Yes	---
CRVFAS-14R/MVS/EM				120-277V	0-10V	Yes	Microwave
CRVFAS-19R-32-9CCT-120-W	19"	150W Incandescent	32W	120V	TRIAC/ELV	---	---
CRVFAS-19R-32-9CCT-UNV-W				120-277V	0-10V	---	---
CRVFAS-19R-32-9CCT-UNV-W/MVS				120-277V	0-10V	---	Microwave
CRVFAS-19R-32-9CCT-UNV-W/EMBB				120-277V	0-10V	Yes	---
CRVFAS-19R/MVS/EM				120-277V	0-10V	Yes	Microwave

CURV Decorative - CRVFAD

Catalog Number	Size	Equivalency	Input Wattage	Input Voltage	Dimming Protocol	Emergency Battery	Sensor
CRVFAD-12R-16-9CCT-120-BN	12"	75W Incandescent	16W	120V	TRIAC/ELV	---	---
CRVFAD-12R-16-9CCT-UNV-BN				120-277V	0-10V	---	---
CRVFAD-12R-16-9CCT-UNV-BN/MVS				120-277V	0-10V	---	Microwave
CRVFAD-12R-16-9CCT-UNVT-BN/EM				120-277V	TRIAC/ELV	Yes	---
CRVFAD-12R/MVS/EM				120-277V	0-10V	Yes	Microwave
CRVFAD-14R-20-9CCT-120-BN				14"	125W Incandescent	20W	120V
CRVFAD-14R-20-9CCT-UNV-BN	120-277V	0-10V	---				---
CRVFAD-14R-20-9CCT-UNV-BN/MVS	120-277V	0-10V	---				Microwave
CRVFAD-14R-20-9CCT-UNVT-BN/EM	120-277V	TRIAC/ELV	Yes				---
CRVFAD-14R/MVS/EM	120-277V	0-10V	Yes				Microwave
CRVFAD-18R-32-9CCT-120-BN	18"	150W Incandescent	32W				120V
CRVFAD-18R-32-9CCT-UNV-BN				120-277V	0-10V	---	---
CRVFAD-18R-32-9CCT-UNV-BN/MVS				120-277V	0-10V	---	Microwave
CRVFAD-18R-32-9CCT-UNV-BN/EM				120-277V	0-10V	Yes	---
CRVFAD-18R/MVS/EM				120-277V	0-10V	Yes	Microwave