





TRUE, UL 924 CERTIFIED EMERGENCY LED TUBE

Stays lit when it matters most.

Wiring made easy.

The integrated driver on this UL Type B lamp enables ballast bypass so that you can wire directly to line voltage without worrying about ballast compatibility.





Status indication and testing.

A manual testing switch is included with the SBR10 to make routine testing a breeze, and a light indicator next to the on/off switch will be solid red when battery is charging and solid green when the battery is fully charged.

Emergency battery can last for a minimum of 90 minutes and up to as much as 200 minutes.










U

tery backup time



Field-adjustable CCT.

Boasting three selectable color temperatures, the SBR10 is designed for 120-277V use and comes in a 14.5W model that delivers 1800 lumens under normal operating conditions and 400 lumens while in emergency mode.

Built to last.

Designed with durable, shatterproof polycarbonate, the SBR10's rugged construction is NSF certified and won't discolor over time.



Ordering Matrix

| Family | Length/Wattage | | Material | | CRI/Color Temp | | Voltage | | Installation Type | |
|-----------|----------------|-------------|----------|---------|----------------|--------------------------------|---------|----------|-------------------|------------------------|
| SBR10 | | | | | | | | | | |
| Saber T10 | Blank | 4ft., 14.5W | Blank | Plastic | Blank | 80 CRI, 3500K, 4000K, 5000K | Blank | 120-277V | Blank | Type B, Ballast Bypass |



RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty