

**RAB**<sup>®</sup>

**HAZLED**



Built for your hazardous environments.

The rugged, versatile HAZLED.



100,000-HOUR LED LIFESPAN



IP66 RATING



Certified to UL standard 1598 and 844.



5-YEAR NO COMPROMISE WARRANTY

RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty)

## Built Tough



Certified for:

- Class I Division 2 (Groups A, B, C, D)
- Class II Division 1 (Groups E, F, G)
- Class II Division 2 (Groups F, G)
- Class III

- A** "Hands free" tether for safe, easy wiring
- B** Temperature rating of T4A
- C** Corrosion-resistant aluminum
- D** Resistant to shock and vibrations (3G)
- E** Available with clear lens, frosted lens, clear globe, frosted globe
- F** Wire guard included for additional protection

## Secure installations for all facility areas.

The HAZLED is available with four mounting options for use throughout an entire site:



Surface and Pendant Mount\*

*\*Remove yoke for pendant mount.*



Ceiling Mount



Stanchion Mount



Wall Mount

## Ordering Matrix

Product Family	Wattage		Color Temp		Mount		Finish		Lens/Globe		Voltage	
HAZLED	30	30W	Blank	5000K	Blank	Surface/Pendant	Blank	Gray	CF	Clear Flat Lens	Blank	120-277V, 0-10V dimming
	60	60W			C	Ceiling			FF	Frosted Flat Lens	/480	480V*
	80	80W			S	Stanchion			CG	Clear Globe		
	120	120W			WM	Wall Mount			FG	Frosted Globe		

\*480V for 120W only