

SAGE: SLOT Landscape Lighting



SA-SLWP
Wall Sconce



SA-SLB
Bollard



PROJECT: _____

DATE: _____

TYPE: _____

PREPARED BY: _____



KEY FEATURES

- SAGE REED is available in two models:
SA-SLWP: Wall pack
SA-SLB: Bollard
- CCT: 3000K or RGBW color tuning with Lightcloud Blue
- RGB models directly connect to the Lightcloud Blue mobile app via Bluetooth. No Gateway or Hub required
- Voltage Rating: 120-277V (Round & Square), 120V (Line)
- IP65 rated
- 5-year, limited warranty

Color-tunable, architectural landscape lighting



IP65
IP RATING



* Select Models

PERFORMANCE

SA-SLWP/RGB	RED	GREEN	BLUE	2200K	2700K	3000K	3500K	4000K	SA-SLWP	3000K
INPUT WATTS	2.27W	2.26W	2.25W	3.05W	3.41W	3.74W	5.32W	7.95W	INPUT WATTS	8.27W
LUMENS	13	33	5	35	53	69	145	307	LUMENS	332
EFFICACY	5.7	14.6	2.2	11.5	15.5	18.4	27.3	38.6	EFFICACY	40.1
CRI				54	72	81	96	84	CRI	85
VOLTAGE RATINGS	120-277V								VOLTAGE RATINGS	120-277V

SA-SLB/RGB	RED	GREEN	BLUE	2200K	2700K	3000K	3500K	4000K	SA-SLWP	3000K
INPUT WATTS	2.38W	2.38W	2.37W	3.23W	3.65W	3.89W	5.01W	9.22W	INPUT WATTS	9.96W
LUMENS	8	18	3	21	33	39	71	186	LUMENS	262
EFFICACY	3.4	7.6	1.3	6.5	9.0	10.0	14.2	20.2	EFFICACY	26.3
CRI				62	77	82	95	90	CRI	85
VOLTAGE RATINGS	120-277V								VOLTAGE RATINGS	120-277V

Lifespan

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

TECHNICAL SPECIFICATIONS

CONSTRUCTION

Cold Weather Starting

Minimum starting temperature is -40°C (-40°F)

Maximum Ambient Temperature

Suitable for use in up to 45°C (113°F)

Housing

Die-cast aluminum

Mounting

SA-SLWP: Octangular J-Box or bracket for the wall-mount
(J-Box not provided)

SA-SLB: 3pcs anchor bolts for mounting

Lens

Polycarbonate

Gaskets

Silicone

Green Technology

Mercury and UV free. RoHS-compliant components.

Finish

Formulated for high durability and long lasting color. Available matte bronze finish.

IP Rating

Ingress protection of IP65 for dust and water

COMPLIANCE

UL Listed

Suitable for wet locations

ELECTRICAL

Drivers:

Constant Current, Class 2, 120V, 50/60 Hz

SA-SLWP: 0.07A@120V, 0.04A @208V, 0.04A @240V, 0.04A @277V

SA-SLB: 0.08A@120V, 0.05A @208V, 0.04A @240V, 0.04A @277V

Surge Protection

2kV (L-N)

THD / Power factor:

MODEL#	THD	PF	THD	PF
	120V		277V	
SA-SLWP	8.6%	99.0%	21.4%	90.3%
SA-SLB	8.5%	99.1%	16.4%	92.7%
SA-SLWP/RGB:				
RED	17.9%	91.7%	35.9%	62.0%
GREEN	17.9%	91.6%	35.7%	61.9%
BLUE	18.1%	91.5%	35.9%	61.9%
2200K	11.7%	96.3%	30.2%	69.6%
2700K	11.2%	96.9%	27.6%	72.1%
3000K	10.7%	97.5%	25.6%	74.9%
3500K	9.9%	98.5%	19.2%	83.3%
4000K	9.4%	99.1%	13.4%	90.4%

ELECTRICAL

THD / Power factor:

MODEL#	THD	PF	THD	PF
	120V		277V	
SA-SLB/RGB:				
RED	15.6%	90.2%	19.9%	49.3%
GREEN	15.3%	90.4%	20.1%	49.1%
BLUE	15.8%	90.1%	20.0%	48.9%
2200K	13.1%	95.1%	17.5%	59.1%
2700K	12.9%	96.0%	16.1%	63.5%
3000K	12.8%	96.3%	15.7%	65.6%
3500K	12.4%	97.5%	13.4%	73.8%
4000K	8.7	99.1%	9.5%	88.9%

Note: All values are typical (tolerance +/- 10%)

LED CHARACTERISTICS

LEDS

Long-life, high-efficacy, surface-mount LEDs

Color Uniformity

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standards for Specifications for the Chromaticity of Solid State Lighting (SLL) Products, ANSI C78.377-2017.

Color Temperature

Default: 3000K

/RGB models are adjustable using the Lightcloud Blue mobile app

Tunable White 2200K - 4000K

16+ million RGB color

LIGHTCLOUD BLUE

LIGHTCLOUD BLUE ENABLED

Lightcloud Blue (LCB) is a Bluetooth Mesh wireless lighting control System that allows you to control RAB's various compatible devices. With RAB's patented Rapid Provisioning technology, devices can be quickly and easily commissioned for residential and large commercial applications using the Lightcloud Blue mobile app. Each device in a system can communicate with any other device, eliminating the need for a Gateway or Hub and maximizing the control system's reach.

DLC system - N1XMLOEATBA (Interior); NHCZ2BIA17L (Exterior)

Learn more at www.lightcloud.com

OTHER

Warranty

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


SAGE: SLOT Landscape Lighting



DIMENSIONS


SA-SLWP

Weight: 2.71 lbs
Weight: 3.09 lbs (RGB Model)



SA-SLB

Weight: 4.32 lbs
Weight: 4.41 lbs (RGB Model)



ORDERING MATRIX

SAGE (SLOT)

FAMILY		SHAPE	TYPE		CCT	FINISH	DRIVER	OPTIONS			
SA	-	SL									
		SL	Slot	WP B	Wall Sconce Bollard	BLANK BLANK	3000K 2200K-4000K* Tunable White	BLANK Matte Bronze	BLANK 120-277V	Blank /RGB	No Option 16+ million colors

* Applies to RGB models only