

RAB®

SLIM



FIELD ADJ.



ON/OFF
PHOTOCELL



ADJUSTABLE
THROW



Certified by DarkSky.org




Exceptional performance
with precise optics control.
SLIM wall packs—with DarkSky-certified models.


Options to match all your needs.

The SLIM family offers four footprints to match your specific application's needs, ideal for anything from walkways to loading docks. Pair that with field-adjustable CCT and wattage, and you get complete control over your lighting design.


XXS/XS





S



M



L



5000K

4000K

3000K



FEATURE PAGE



100,000-HOUR
LED LIFESPAN



LIGHTCLOUD
CONTROLLER



0-10V



120-277V



COMPLIANT



Certified by DarkSky.org



5-YEAR,
NO-COMPROMISE
WARRANTY

RAB's warranty is
subject to all terms
and conditions found at
rablighting.com/warranty

It's easy being green.

The SLIM's new design is lighter and thinner than its predecessor, and it houses a suite of features designed for sustainability. Its raw aluminum back foregoes any anodization or chemical coatings, the full cutoff optics reduce light pollution, and its integrated photocell helps reduce energy costs. Models with static 3000K CCT are available that are DarkSky certified and DLC LUNA listed.



ON/OFF
PHOTOCELL



Certified by DarkSky.org

Precision meets versatility.

The high-output SLIM rewrites the rules of wall pack lighting with its innovative 5-position aiming system. From -20° to $+20^{\circ}$, you can direct light exactly where you need it while maintaining full cutoff compliance.



Intelligent design for easy installs.

With convenient, top-access latches, the SLIM allows for simple, quick wiring and maintenance.



Available with smart controls.

SLIM is offered with a factory-installed Lightcloud or Lightcloud Blue Controller for compatibility with our powerful, wireless, lighting control systems.

Lightcloud®



Ordering Matrix

Product Family	Wattage	Color Temp	Finish	Driver	Options
SLIM					
XXS	7/5/3.5W	Blank	3000/4000/5000K CCT Adjustable	Blank	No Option
XS	25/18/12W				Lightcloud
S	38/28/18W	Y	3000K (Static)	Blank	Lightcloud Blue
M	55/41/27W			120-277V, 0-10V Dimming	
L	60/45/29W				